

EV Charging Cable - 32A Three Phase T2 Female-CEE

A portable three phase mains charger for use on any BEV (Battery Electric Vehicle) and PHEV (Plug-in Hybrid Electric Vehicle) that uses a Type 2 connector. Suitable for use with a 32A three phase workshop power supply, with a maximum power output 22kW. Supplied in a zip-up carry-case so that it can be kept safely and tidily in the vehicle when not in use.



Additional Information

- 5m long BEV/PHEV charging cable with controller, featuring a Type 2 vehicle plug (female) to 32 amp three phase Commando plug (red) for workshop charging, complete with carry bag.
- Three phase voltage up to 415V AC, for rapid charging up to 22kW. Variable charge rates: 8A, 10A, 13A, 16A, 32A.
- Tested to 4,000V AC. Operating temperature: -20C to +50C. Connectors made from durable polycarbonate with copper alloy contacts. Control unit: overcurrent, overvoltage and overheat protection. Mains plug: short circuit & temperature protection.
- Applications include: Audi, BMW, Hyundai, Jaguar, Kia, Lucid Air, Mercedes-Benz, MINI, Nissan Leaf (2018), Porsche, Range Rover P400e, Renault, Smart, Tesla, Toyota, Volkswagen, Volvo.
- Gun IP65, control box IP54 rated, IEC, TUV, CE & UKCA, REACH, RoHS compliant. IEC62752, IEC61851.

<http://lasertools.co.uk/product/9109>

