| EXIDE TECHNOLOGIES | CUSTOMER D | Printed: 17/03/2022 Product Management Transportation Europe |
|--|---|--|
| Central Article Code: | C43009D01-A | Created: 02/09/2005 |
| Local Code: | 4503 | Modified: 15/12/2020 |
| | | |
| | | Final Outlook C4301-A Approval date 15/03/2011 |
| PERFORMANCES | | CONTAINER |
| Voltage (V): | 12 V | Type: C43 WHITE |
| C20 (Ah): | 9.0 10 h | Hold Down: B0 |
| Cranking (A): | 85 EN | H.D. Adapter: No |
| Charge: | DRY | COVER |
| Fechnology: | Vented/Flooded | Type: Motorbike (B ventilati BLACK |
| Grid: | Low Sb | Polarity: ETN 1 |
| Vibration: | Not Defined | Terminals: M06 |
| Endurance: | Not Defined | Terminal Adapter: No |
| | | SOCI: No |
| OTI | | Ventilation: Moto-B |
| STD. DIMENSIONS Length (mm ± 2): 135 | | Filter: No Lateral Plug: No |
| Width (mm ± 2): | 75 | |
| Height (mm \pm 2): | 140 | PLUGS |
| Total Weight (kg ± 5% | | Type: 6 x Moto Plug RED |
| | , | HANDLES |
| | | Type: None |
| | | OTHERS |
| end users is forbidden by E | d with bottles of sulphuric acid. Sale of acid to u.Reg.1148/2019. Dry batteries must be filled | Degassing Tube: No |
| with acid before delivery to | end users lues. Tolerances are according to EN50342 | |

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.