


CUSTOMER DATASHEET


Printed: 17/03/2022


Product Management Transportation Europe

C49013D01-A Central Article Code: Created: 02/09/2005

Local Code: 4521 Modified: 15/12/2020







Final Outlook C4901-A Approval date 15/03/2014

PERFORMANCES				
Voltage (V):	12 V		Type:	
C20 (Ah):	14.0	10 h	Hold Dov	
Cranking (A):	130	EN	H.D. Ada	
Charge:	DRY			
Technology:	Vented/F	looded	Type:	
Grid:	Low Sb		Polarity:	
Vibration:	Not Defin	ed	Terminals	
Endurance:	Not Defin	ed	Terminal	
			SOCI:	
			Ventilatio	
STD. DIMENSIONS			Filter:	
Length (mm ± 2):	135		Lateral P	
Midth (mm 1 2)	00			

C49 WHITE B0 wn:

CONTAINER

COVER

apter: No

Motorbike (A ventilati BLACK ETN₀ s: M08 Adapter: No Moto-A n:

No lug: No

Length (mm ± 2):	135		
Width (mm ± 2):	90		
Height (mm ± 2):	165		
Total Weight (kg ± 5%):	4.60		

RED 6 x Moto Plug Type:

HANDLES

PLUGS

None Type:

OTHERS Degassing Tube: No

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

EAC certified