


CUSTOMER DATASHEET


Printed: 17/03/2022


Product Management
Transportation Europe

Central Article Code: C45015D01-A Created: 02/09/2005

Local Code: 4525 Modified: 15/12/2020







Final Outlook C4501-A Approval date 01/05/2010

PERFORMANCES Voltage (V): 12 V C20 (Ah): 12.0 10 h 165 ΕN Cranking (A): DRY Charge: Vented/Flooded Technology: Grid: Low Sb Vibration: Not Defined Endurance: Not Defined

Type:	C45	WHITE
Hold Down:	B0	

CONTAINER

COVER

Motorbike (A ventilati BLACK

Hold Down: B0 H.D. Adapter: No

Type:

Polarity: ETN 1
Terminals: M06
Terminal Adapter: No
SOCI: No
Ventilation: Moto-A

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 135

 Width (mm \pm 2):
 80

 Height (mm \pm 2):
 160

 Total Weight (kg \pm 5%):
 4.20

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

Type: 6 x Moto Plug RED

HANDLES

Type: None

OTHERS

Degassing Tube: No

EAC certified