


CUSTOMER DATASHEET


Printed: 17/03/2022


Product Management
Transportation Europe

Central Article Code: C75013F01-A Created: 26/10/2006

Local Code: 4907 Modified: 15/12/2020







Final Outlook C7501-A Approval date 01/12/2009

PERFORMANCES			CONTAINER			
Voltage (V):	12 V		Type:	C75	BLACK	
C20 (Ah):	12.0	10 h	Hold Down:	B0		
Cranking (A):	190	EN	H.D. Adapter:	No		
Charge:	DRY		COVER			
Technology:	AGM		Type:	Motorbik	e (independ BLACK	
Grid:	Ca/Ca		Polarity:	ETN 1		
Vibration:	Not Defined		Terminals:	M04		
Endurance:	Not Defined		Terminal Adapter:	No		
			SOCI:	No		
			Ventilation:	Sealed		
STD. DIMENSIONS			Filter:	No		
Length (mm ± 2):	150		Lateral Plug:	No		
Width (mm ± 2):	70		PLUGS			
Height (mm ± 2):	145		Type: 1 x Vent		BLACK	
Total Weight (kg ± 5%):	4.10		HANDLES			
			Type: None			
			OTHERS			
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No		
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.						
			EAC certified			