


CUSTOMER DATASHEET


Printed: 17/03/2022


Product Management
Transportation Europe

Central Article Code: C55018F02-A Created: 26/10/2006

Local Code: 4916 Modified: 15/12/2020







Final Outlook C5502-A Approval date 01/12/2009

PERFORMANCES			CONTAINER				
Voltage (V):	12 V		Type:		C55	BLACK	
C20 (Ah):	10.0	10 h	Hold Do	wn:	B0		
Cranking (A):	150	EN	H.D. Ad	apter:	No		
Charge:	DRY		COVER				
Technology:	AGM		Type:		Motorbike	(independ BLACK	
Grid:	Ca/Ca		Polarity:		ETN 1		
Vibration:	Not Defined		Termina	ls:	M04 : No		
Endurance:	Not Defined		Termina	l Adapter:			
			SOCI:		No		
			Ventilation	on:	Sealed		
STD. DIMENSIONS			Filter:		No		
Length (mm ± 2):	150		Lateral F	Plug:	No		
Width (mm ± 2):			PLUGS				
Height (mm ± 2):	130		Type:	1 x Vent		BLACK	
Total Weight (kg ± 5%):	3.90		HANDLES				
			Type:	None			
			OTHERS				
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube: No				
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.							
				EAC Certified			