

## **CUSTOMER DATASHEET**


Printed: 18/03/2022


27/10/2006


Product Management
Transportation Europe

Central Article Code: C53019F02-A Created:

Local Code: 4976 Modified: 15/12/2020







Final Outlook C5302-A Approval date 01/12/2009

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C53	BLACK
C20 (Ah):	9.0	10 h	Hold Down:	B0	
Cranking (A):	145	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	AGM		Type:	Motorbik	ke (independ BLACK
Grid:	Ca/Ca		Polarity:	ETN 1	
Vibration:	Not Defined		Terminals:	M12	
Endurance:	Not Defined		Terminal Adapter:	No	
			SOCI:	No	
			Ventilation:	Sealed	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	150		Lateral Plug:	No	
Width (mm ± 2):	90		PLUGS		
Height (mm ± 2):	95		Type: 1 x Vent		BLACK
Total Weight (kg ± 5%):	3.40		HANDLES		
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users		Degassing Tube:	No		
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.			YTZ10S		
1, 2 =	,		EAC certified		