




TECHNICAL DATASHEET

Printed: 27/01/2015
Product Management
Transportation Europe

Central Article Code:C56020F05-ACreated:18/11/2011ETN Code or Other:YTX14L-BSModified:04/03/2014







Final Outlook C5605-A Approval date 15/12/2011

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C56	BLACK
C20 (Ah):	12.0	10 h	Hold Down:	В0	
Rc (min):	0		H.D. Adapter:	No	
Cranking (A):	200	EN	OOVED		
Vibration:	n: Not Defined		COVER		
Endurance:			Type:		
Charge:	DRY		Polarity:	ETN 0	
Technology:	AGM		Terminals:	M04	
Grid:	Ca/Ca		Terminal Adapter:	Harley-D K	Cit
			SOCI:	No	
WEIGHT AND STD. DIMENSIONS			Ventilation:	Sealed	
			Filter:	No	
Battery Weight (kg ±	5%): 4.5		Lateral Plug:	No	
Volume acid (I ± 5%): .7 Length (mm ± 2): 150			PLUGS		
Width (mm ± 2):	90		Type: 1	x Vent	BLACK
Height (mm ± 2): 145			HANDLES		
			Type: N	lone	
		OTHERS			
			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					