	CUSTOMER [ATASHEFT Printed: 18/03/2022 Product Management
TECHNOLOGIES		Transportation Europe
Central Article Code:	C71035F05-A	Created: 02/11/2006
Local Code:	4994	Modified: 15/12/2020
DEB		CONTAINER
	12 V	
Voltage (V): C20 (Ah):	12 v 21.0 10 h	Type: C71 BLACK Hold Down: B0
Cranking (A):	350 EN	H.D. Adapter: No
Charge:	DRY	
Technology:	AGM	
Grid:	Ca/Ca	Type:Motorbike (independ BLACKPolarity:ETN 0
Vibration:		Terminals: M04
Endurance:	Not Defined	Terminal Adapter: Harley-D Kit
	Not Defined	SOCI: No
		Ventilation: Sealed
STD. DIMENSIONS		Filter: No
Length (mm ± 2):	205	Lateral Plug: No
Width (mm ± 2):	90	PLUGS
Height (mm ± 2):	165	Type: 1 x Vent BLACK
Total Weight (kg ± 5%):	5.80	HANDLES
		Type: None
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users		OTHERS Degassing Tube: No
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.		YTX24HL-BS
and applicable European Re	guiauons.	EAC certified
		anged without notice. Any use, conv or distribution has to be authorised in

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.