


CUSTOMER DATASHEET


Printed: 18/03/2022


Product Management
Transportation Europe

Central Article Code: C66017G04-A Created: 02/09/2005

Local Code: 80019 Modified: 03/05/2018







Final Outlook C6604-A Approval date 01/10/2005

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 19.0 20 h Cranking (A): 170 EN

Charge: CHARGED

Technology: GEL

Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 250 cycles@100%

CONTAINER

Type: C66 GREY MEDIUM

Hold Down: B0 H.D. Adapter: No

COVER

Type: DIN GREY MEDIUM

Polarity: ETN 0
Terminals: M11
Terminal Adapter: No
SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 185

 Width (mm \pm 2):
 80

 Height (mm \pm 2):
 170

 Total Weight (kg \pm 5%):
 6.50

PLUGS

Type: 6 x Valve+Cover GREY MEDIUM

HANDLES

Type: None

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.