

PULSE 30 EVO



Pulse n/n
Tronic



DESCRIPTION

Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PBCA, EFB, Li-12V/24V batteries with LCD display.

Charging and maintenance programs in Pulse Tronic dedicated to the technology of the selected battery. BOOST function for quick charge. Advanced function for charging and maintenance of batteries at low temperatures. Activation of the RECOVERY function enables resetting of sulphated batteries. Tests the vehicle alternator and battery. Continuous and reliable power supply source during battery changes. Simplified use and immediate display of the parameters thanks to the LCD display.

Features:

- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge of the batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- TEST function for battery, starting and alternator;
- SUPPLY function for stable power supply during battery changing;
- LCD display;
- Battery voltage selection;
- Protection against overcharge, short circuit and polarity reversal.

Fit with PFC device.

Complete with cables with clamps.



TECHNICAL DATA

CODE CODE 807610	V_{1PH} SINGLEPHASE MAINS VOLTAGE 230 V	F MAINS FREQUENCY 50 / 60 Hz
P CHARGING ABSORBED POWER 369 W	BATTERY CHARGING VOLTAGE 12 / 24 V	A_{EFF} EFFECTIVE CHARGING CURRENT 27 / 15 A



RATED CHAR.CUR.EN60335-2-29
25 / 12 A



QUICK CHARGE/START CURRENT
25 (Boost) A



MIN.RATED REFERENCE CAPAC.
5 Ah



MAX.RATED REFERENCE CAPAC.
400 Ah



PROTECTION DEGREE
IP33




DIMENSIONS (LxWxH)
9,2x20x33 cm



WEIGHT
3,11 kg

ON REQUEST ACCESSORIES



HOLDING BRACKET KIT
803086



MAGNET KIT
803087



TROLLEY - DIAGNOSTIC
803077

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL