

DYNAMIC 620 START



DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage and starting all kinds of cars, vans and light trucks.

Features:

- choice of normal charge, quick charge (BOOST), quick start
- timer for quick charge
- display of charging and starting current
- protection against overloads and polarity reversal.



TECHNICAL DATA

CODE	CODE 829384	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P_{CHARGE}	CHARGING ABSORBED POWER 2 kW	P_{START}	STARTING ABSORBED POWER 10 kW		CHARGE AND STARTING VOLTAG. 12 / 24 V
A_{EFF}	EFFECTIVE CHARGING CURRENT 90 A	A_{EN}	RATED CHAR.CUR.EN60335-2-29 70 A	A_{1V/C}	START CUR.1V/C EN60335-2-29 360 A
A_{START MAX}	MAX STARTING CURRENT 570 A		MIN.RATED REFERENCE CAPAC. 20 Ah		MAX.RATED REFERENCE CAPAC. 1550 Ah
	ADJUSTMENT POSITIONS 4		DIMENSIONS (LxWxH) 36,5 x 46 x 75,5 cm		WEIGHT 24 kg
BAR CODE	EAN CODE 800489773286 2		PIECES/PALLET 9 pz/pallet		PIECES/PALLET-B 6 pz/pallet B

ON REQUEST ACCESSORIES



FUSES 100A 20 PCS
802029

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST