


CUSTOMER DATASHEET


Printed: 18/02/2022


Product Management
Transportation Europe

Central Article Code: L02067C69-C Created: 30/01/2014

Local Code: EL600 Modified: 01/09/2021







Final Outlook L0269-C Approval date 15/02/2014

	7			N A	A	N		_	c
	RF	u	ĸ	IVI	А	N	u	⊏;	č

Voltage (V): 12 V

C20 (Ah): 60.0 20 h Cranking (A): 640 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: VW Requirement (MHF)

CONTAINER

Type: L02 BLACK Hold Down: B13

H.D. Adapter: No

COVER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 1 Filter at Left

Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 242

 Width (mm \pm 2):
 175

 Height (mm \pm 2):
 190

 Total Weight (kg \pm 5%):
 17.00

PLUGS

Type: 1 x Vent Sealed PSL-OE ha BLACK

HANDLES

Type: 1 x PSL OE Integrated BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.