

# Product Data Sheet

## Mobil Chain Saw Oil Splash Resistant Lubricant

### Product Description

Mobil Chain Saw Oil is a specialist chain saw oil which resists splash-creep, throw-off and drip. It is based on solvent refined paraffinic oils and it contains additives to enhance load carrying, anti-rust and adhesive properties.

### Benefits

Mobil Chain Saw Oil offer the following benefits:

- Improved lubrication and less wear in high speed rotating mechanisms subject to oil depletion from centrifugal force
- Reduced oil usage through excellent adhesive properties
- The load carrying and anti-rust materials make it an ideal circulating oil
- Protects ferrous surfaces against rusting

### Application

Mobil Chain Saw Oil is recommended for all types of chain saws including slow moving external gears and chains where minimum oil wastage is desirable.

## Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

## Typical Characteristics

---

### Mobil Chain Saw Oil

ISO Viscosity Grade	100
Viscosity, cSt at 40°C	90/100
Pour Point, °C	-9
Flash Point, °C	234

---

Due to continual product research and development, the information contained herein is subject to change without notice.

---

**Mobil Oil Company Limited**  
**Acting as Agent for Mobil Lubricants UK Limited**  
**ExxonMobil House, Ermyn Way**  
**Leatherhead, Surrey, KT22 8UX**  
**Telephone: 01372 22 2000**

