## Prima


## **APBX 8 DS**

Passive Sealed Sub Box 500 W

TECHNICAL SPECIFICATIONS		
Component		Passive Sealed Sub Box
Subwoofer size	mm (in.)	200 (8)
Power Handling	W peak W continuos	500 250
Impedance	Ω	4+4
Sub box size	mm (in.)	374 (14.72) x 131 (5.16) x 334 (13.5)
Weight of one component	kg (lb.)	6,22 (13.71)
Magnet		High density flux ferrite
Cone		Water-repellent pressed paper
Subwoofer Voice coil Ø	mm (in.)	40 (1.57)




- Ultra-low profile (5.16 in. / 131 mm) box with sealed design perfectly tuned to fully exploit the APS 8 D driver.
- $2S^2$  (2 Sides/2 Sounds) design provides the ability to choose between Down-Firing mounting to increase the low-frequency extension and Up-Firing install to obtain more punch and definition.
- Leveling feet with velcro inserts included for a secure grip with the carpet while maintaining easy removal.
- SSP (Sub Smart Plug) features both traditional push contacts and a Plug-&-Play terminal block to easily configure the impedance as required and provides a quick release.
- Rounded corners allow easy positioning in the trunk and act as reinforcement to reduce enclosure resonance.
- Special designed cone-dustcap-basket geometry which guarantees a long linear excursion capability (9 mm, one-way).
- Massive driver motor assembly, optimized with FEM (Finite Element Modeling) for perfect control under high excursion conditions.
- Water-repellent pressed paper 8 in. cone, featuring a profile developed with FEM simulation and optimized with the Klippel Scan Vibrometer.
- Specifically developed to be combined with either AP1 D mono or AP4.9 bit/AP4 D (2 CH bridged) amplifiers taking advantage of the bass boost feature and integrated parametric equalizer of the built-in DSP.
- 10 Sturdy metal grid included for a total protection of the subwoofer driver.



elettromedia.com

374 mm | 334 mm | 109 mm | 131 mm

14.72 in. 13.15 in. 4.29 in. 5.16 in.





KLIPPEL