

APK 130 2 WAY SYSTEM

- 1 AP1 tweeter with 26 mm diameter diaphragm combined with a wide-roll surround provides maximum efficiency and reduced resonance frequency.
- 2 AP 1 tweeter with acoustic lens designed to compensate for and fine tune the in-car frequency response anomalies in the 10kHz-13kHz bandwidth caused by restrictive OEM grilles in critical OEM placements.
- 3 APCX TW very compact tweeter passive crossover optimised for OEM Integration featuring an attenuation switch (0 dB, +2dB) to tune the in-car response according to different installation conditions.
- 4 Passive crossovers are supplied with "OEM Integration compliant" fast-on connectors. The ends, different in each of the two poles, eliminate any possible connection errors and speed up the required installation time.
- 5 AP 5 woofer with 32 mm pure copper voice coil, for high power handling and outstanding low frequency control.
- 6 AP 5 woofer with water-repellent treated paper cone, featuring a profile developed with FEM (Finite Element Method) simulation technology and optimized with the Klippel R&D Scan Vibrometer.
- 7 AP5 woofer with reduced mounting depth, providing ease of installation in OEM placements.
- 8 AP5 woofer with TPU (Thermoplastic Polyurethane) surround, featuring the exclusive shallow "Triple Wave" profile, for maximum excursion linearity.
- 9 AP 5 woofer with compact basket, protected by abrasion-resistant and scratch-proof coating, the motor affixed with damping epoxy adhesive.
- 10 AP 5 woofer with high current fast-on terminal with double contact on positive and negative poles for high flexibility and quick connection. The terminal features a temperature resistant plastic cover, protecting it against accidental short circuits.
- 11 Developed with the KLIPPEL suite.

* Grille included

TECHNICAL SPECIFICATIONS

Component		2-way System
Size	mm (in.)	Woofer 130 (5) Tweeter 26 (1)
Power Handling	W peak	225
	W continuos	75
Impedance	Ω	4
Frequency Response	Hz	70 ÷ 20k
Crossover type		HP @ 3,5 kHz - 6 dB Oct
Component adjustment	dB	+2; 0
Woofer Magnet size	mm	85 x 40 x 13
D x d x h	(in.)	(3.35 x 1.57 x 0.51)
Tweeter Magnet size	mm	19 x 13
D x d x h	(in.)	(0.75 x 0.12)
Weight of one speaker	kg (lb)	Woofer 0,65 (1.43) Tweeter 0,04 (0.09)
Voice Coil Ø	mm (in.)	Woofer 32 (1.26) Tweeter 20 (0.8)

From R&D to final product
KLIPPEL
since 2005



ELECTRO-ACOUSTIC PARAMETERS

D	mm	107
Xmax	mm	±2
Re	Ω	3,1
Fs	Hz	90
Le	mH	0,25
Vas	l	4
Mms	g	9
Cms	mm/N	0,34
BL	T•m	4,6
Qts		0,68
Qes		0,74
Qms		8
Spl	dB	93