



-   
**Power adjustable**
-   
**Intelligent appointment**
-   
**plug and play**
-   
**safety protection**
-   
**superior performance**
-   
**strong and sturdy**
-   
**low-temperature work**
-   
**low energy consumption**

<b>Model</b>	ES16AM25
<b>Rated voltage</b>	230VAC+15% 1ph
<b>Rated current</b>	8/10/13/16A
<b>Grid frequency</b>	50/60 Hz
<b>IP protection class</b>	IP65
<b>Operating temperature</b>	-30°C ~ +50°C
<b>Storage temperature</b>	-40°C ~ +85°C
<b>Humidity</b>	Up to 75%, maximum value at 40°C
<b>Altitude</b>	2000 m
<b>Protection</b>	Over-voltage protection/Under-voltage protection/ Over-current protection/Short-circuit protection/ Ungrounded protection/Over-temperature protection/ A+6mA Leakage protectionlph
<b>Operating instruction</b>	LED & Display
<b>Dimensions</b>	200(L)x100(W)x55(H)mm
<b>Total length</b>	5m
<b>Weight</b>	1.75 kg
<b>Connector Type</b>	T2

**Standards** EN 62752:2016/EN IEC 61851-1:2019/  
IEC 62196-1:2014/IEC 62196-2:2016