

T-CHARGE 12 EVO



Pulse n/n
Tronic



TEST



SUPPLY



RECOVERY

- Caricabatterie intelligente e mantenitore di carica elettronico multifunzione con schermo LCD per batterie (Wet, Gel, MF, AGM, Pb-Ca, EFB) da 6/12V d di auto, moto, trattorini, motoslitte, moto d'acqua ecc anche a basse temperature. Completo di cavo con pinze e cavo con occhielli.
- INTELLIGENTE: la tecnologia avanzata Pulse Tronic (made in Telwin) è studiata per aumentare l'efficienza e la durata nel tempo della batteria. Gli 8 step di carica si basano su una diagnosi puntuale, istante per istante, delle condizioni della batteria.
- Funzione TEST alternatore, avviamento e stato di carica della batteria; funzione SUPPLY per l'alimentazione continua durante i cambi batteria e non perdere le memorie del veicolo; funzione RECOVERY per rigenerare le batterie solfatate allungandone la vita tramite un processo ad impulsi.
- SICURO: le numerose protezioni (sovraccarico, cortocircuito, inversione di polarità) garantiscono massima sicurezza all'operatore e integrità alla batteria.
- FACILE E COMPATTO: collega T-Charge alla batteria e scegli la funzionalità da usare, al resto pensa lui. Visualizzazione immediata del livello di carica. Grazie alle dimensioni e al peso ridotti, T-Charge può essere trasportato e posizionato dovunque, anche dove lo spazio è limitato.

DESCRIPTION

Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PbCa, EFB, Li 6/12V batteries with LCD screen.

Charging and maintenance programs in Pulse Tronic dedicated to the technology of the selected battery. Advanced function for charging and maintenance of batteries at low temperatures. Activation of the RECOVERY function enables resetting of sulphated batteries. Tests the vehicle alternator and battery. Continuous and reliable power supply source during battery changes. Simplified use and immediate display of the parameters thanks to the LCD screen.

Features:

- Automatic charging and maintenance in Pulse Tronic based on the technology of the selected battery;
- COLD function for charging and maintenance of batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- TEST function for battery, start-up and alternator;
- SUPPLY function for stable power supply during battery changing;
- LCD screen;
- Protection against overloads, short circuit and polarity reversal.

Complete with cable with clamps and cable with eyelets.



TECHNICAL DATA

CODE	CODE 807578	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P	CHARGING ABSORBED POWER 55 W		CHARGING VOLTAGE 6 / 12 V	A_{EFF}	EFFECTIVE CHARGING CURRENT 1 / 4 A
A_{EN}	RATED CHAR.CUR.EN60335-2-29 1 / 4 A		MIN.RATED REFERENCE CAPAC. 2 Ah		MAX.RATED REFERENCE CAPAC. 70 Ah
IP	PROTECTION DEGREE IP65		DIMENSIONS (LxWxH) 17 x 6,5 x 3,5 cm		WEIGHT 0,6 kg



BAR
CODE

EAN CODE
800489798199 4



PIECES/PALLET
432 pz/pallet



PIECES/PALLET-B
288 pz/pallet B

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



BROCHURE

USEFUL LINKS



VIDEO