


TECHNICAL DATASHEET


Printed: 18/11/2014 Product Management Transportation Europe


11/11/2013

21/03/2014

Central Article Code: LB1046C02-A Created: ETN Code or Other: Modified:







Final Outlook LB102-A Approval date 15/02/2014

PERFORMANCES			CONTAINER		
Voltage (V):	12 V	Type:	LB1	GREY DARK	
C20 (Ah):	47.0 20 h	Hold Down:	B13		
Rc (min):	0	H.D. Adapter:	No		
Cranking (A):	450 EN	COVER			
Vibration:	V2 (35Hz/6g/2h)				
Endurance:	E2 (90 cycles@50%)	Type:		I RIGIUGRET DARK	
Charge:	WET	Polarity:	ETN 0		
Technology:	Vented/Flooded	Terminals:	EN taper post		
Grid:	Ca/Ca	Terminal Adapter:	No		
WEIGHT AND CTD DIMENSIONS		SOCI:	No		
WEIGHT A	AND STD. DIMENSIONS	Ventilation:	Central		
		Filter:	2 Filters		
Battery Weight (kg ±	•	Lateral Plug:	Standard	Right side BLACK	
Volume acid (I ± 5%):	2.8	shape			
Length (mm ± 2):	207	PLUGS			
Width (mm ± 2): 175		Type: 1	x Vent Sealed	PSL- GREY DARK	
Height (mm ± 2):	175	HANDLES			
		Type: 1	x PSL AM	GREY DARK	
			OTHERS		
		Degassing Tube:	No		
All figures show nominal EN50342 and applicable	values. Tolerances are according to European Requlations.				