

## **CUSTOMER DATASHEET**

Printed: 16/02/2022

Product Management
Transportation Europe

Central Article Code:

S68065C06-A

Created:

24/02/2020

Local Code:

EA681

Modified:

18/12/2020

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	S68	BLACK
C20 (Ah):	68.0	20 h	Hold Down:	B13	
Cranking (A):	650	EN	H.D. Adapter:	B3/B13 to B14	BLACK
Charge:	WET		COVER		
Technology:	Vented/Flo	Vented/Flooded		Flat/Press	BLACK
Grid:	Ca/Ca		Polarity:	ETN 1	
Vibration:	V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%)		Terminals:	EN taper post	
Endurance:			Terminal Adapter:	No	
	( )	<b>O</b> * /	SOCI:	No	
			Ventilation:	Independent	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	277		Lateral Plug:	No	
Width (mm ± 2):	175		PLUGS		
Height (mm ± 2):	190		Type: 2 x Gr24-5	SP68	BLACK
Total Weight (kg ± 5%	17.00		HANDLES		
			Type: 1 x SP68		BLACK
		OTHERS			
			Degassing Tube:	No	
All figures show nominal va and applicable European R		according to EN50342			
			C.O. from S68065C04-A (Grey to Black)		