




## TECHNICAL DATASHEET

Printed: 18/11/2014
Product Management
Transportation Europe

Central Article Code: L00041C04-A Created: 04/11/2013 ETN Code or Other: Modified: 04/03/2014







Final Outlook L0004-A Approval date 15/02/2014

PERFORMANCES		
Voltage (V):	12 V	
C20 (Ah):	44.0	20 h
Rc (min):	0	
Cranking (A):	400	EN
Vibration:	V1 (35Hz/3g/2h)	
Endurance:	E1 (180 cycles@25%)	
Charge:	WET	
Technology:	Vented/Flooded	
Grid:	Ca/Ca	
WEIGHT AND STD. DIMENSIONS		

Battery Weight (kg ± 5%): 10.6

Volume acid (l ± 5%): 2.4

Length (mm ± 2): 175

Width (mm ± 2): 175

Height (mm ± 2): 190

Type: L00 BLACK
Hold Down: B13
H.D. Adapter: No

COVER

STS GREY DARK Type: ETN 0 Polarity: Terminals: EN taper post Terminal Adapter: No SOCI: No Ventilation: Central Filter: 1 Filter at Left Lateral Plug: No **PLUGS** 1 x STS **GREY DARK** 

Type: 1 x STS GREY DARK

HANDLES

Type: None

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.