


# **CUSTOMER DATASHEET**


Printed: 16/02/2022


**Product Management** Transportation Europe

LB1041C34-G 10/05/2018 Central Article Code: Created:

Modified: 31/07/2020 Local Code: EB442







**Final Outlook** LB134-G Approval date 01/07/2018

PEF	RFOF	RMA	NCES
	•.		

Voltage (V): 12 V

C20 (Ah): 44.0 20 h 420 ΕN Cranking (A):

WET Charge:

Vented/Flooded Technology:

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

STD. DIMENSIONS

Length (mm ± 2): 207

Width (mm ± 2): 175 Height (mm ± 2): 175 Total Weight (kg ± 5%): 10.60

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type:	LB1	BLACK

B13 Hold Down: H.D. Adapter: No

#### **COVER**

**CONTAINER** 

Type: NPR BLACK

Polarity: ETN 0

EN taper post Terminals:

Terminal Adapter: No SOCI: No Ventilation: Central 2 Filters Filter:

Lateral Plug: Standard Right side BLACK

shape

# **PLUGS**

Type: 1 x NPR (Manifold) **BLACK** 

## **HANDLES**

1 x NPR (Standard) BLACK Type:

### **OTHERS**

Degassing Tube: No