


CUSTOMER DATASHEET

Printed: 16/02/2022


Product Management Transportation Europe


B24033C24-A Created: 17/06/2014 Central Article Code:

Modified: 01/06/2020 Local Code: EB455



Final Outlook B2424-A 15/03/2019 Approval date





PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 45.0 20 h 330 ΕN Cranking (A):

WET Charge:

Vented/Flooded Technology:

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

CONTAINER

COVER

Flat/Screw Integrate BLACK

B24 **BLACK** Type: Hold Down: B0

H.D. Adapter: No

Polarity: ETN 1

Type:

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug:

STD. DIMENSIONS

Length (mm ± 2): 237 Width $(mm \pm 2)$: 127 Height (mm ± 2): 227 Total Weight (kg ± 5%): 11.40

PLUGS

BLACK 6 x M18 Type:

HANDLES

1 x Integrated BLACK Type:

OTHERS

Degassing Tube: No

Used for BOSCH

All figures show nominal values. Tolerances are according to EN50342

and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.