EXIDE TECHNOLOGIES	CUSTOMER I	DATASHEET Printed: 16/02/2022 Product Management Transportation Europe
Central Article Code:	B24033C21-A	Created: 17/06/2014
Local Code:	EB456	Modified: 01/06/2020
		Final Outlook B2421-A Approval date 15/03/2019
PERFORMANCES		CONTAINER
Voltage (V):	12 V	Type: B24 BLACK
C20 (Ah):	45.0 20 h	Hold Down: B0
Cranking (A):	330 EN	H.D. Adapter: No
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Flat/Screw Integrate BLACK
Grid:	Ca/Ca	Polarity: ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals: JIS taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter: No
	\Box (100 cycles $(U \ge 0)$)	SOCI: No
		Ventilation: Independent
STD. DIMENSIONS		Filter: No
Length (mm ± 2):	237	Lateral Plug: No
Width (mm ± 2):	127	PLUGS
Height (mm ± 2):	227	Type: 6 x M18 BLACK
Total Weight (kg ± 5%):	11.30	HANDLES
		<u>,, , , , , , , , , , , , , , , , , , ,</u>
		OTHERS
		Degassing Tube: No
All figures show nominal valu	es. Tolerances are according to EN50342	
and applicable European Reg	guiations.	Used for BOSCH

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.