

## **CUSTOMER DATASHEET**

Printed: 16/02/2022


07/11/2019


Product Management
Transportation Europe


Created:

Central Article Code: G75061C03-A

Local Code: EB558 Modified: 21/11/2019







Final Outlook G7503-A Approval date 15/11/2019

1 EIG OIGH GIGE		
Voltage (V):	12 V	
C20 (Ah):	55.0	20 h
Cranking (A):	620	EN

**PERFORMANCES** 

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

 Vibration:
 V1 (30Hz+/-2Hz/3g/2h)

 Endurance:
 E1 (180 cycles@25%)

	COVER	
Type:	Flat/Press	BLACK

**CONTAINER** 

**BLACK** 

Polarity: ETN 1

Type:

Hold Down: H.D. Adapter:

Terminals: SAE S 3/8" side Terminal

G75

B7

No

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters
Lateral Plug: No

## STD. DIMENSIONS

 Length (mm  $\pm$  2):
 230

 Width (mm  $\pm$  2):
 180

 Height (mm  $\pm$  2):
 186

 Total Weight (kg  $\pm$  5%):
 14.20

**PLUGS** 

Type: 1 x Vent Sealed BLACK

**HANDLES** 

Type: None

**OTHERS** 

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.