


CUSTOMER DATASHEET


Printed: 17/02/2022


Product Management
Transportation Europe

Central Article Code: G65080C01-B Created: 07/11/2019

Local Code: EB858 Modified: 21/11/2019







Final Outlook G6501-B Approval date 15/11/2019

| PERFORMANCES | | CONTAINER | | |
|--|---|-------------------|--------------|-------|
| Voltage (V): | 12 V | Type: | G65 | BLACK |
| C20 (Ah): | 85.0 20 h | Hold Down: | B1 | |
| Cranking (A): | 800 EN | H.D. Adapter: | No | |
| Charge: | WET | COVER | | |
| Technology: | Vented/Flooded | Type: | Flat/Press | BLACK |
| Grid: | Ca/Ca | Polarity: | ETN 1 | |
| Vibration: | V1 (30Hz+/-2Hz/3g/2h) | Terminals: | EN taper pos | t |
| Endurance: | E1 (180 cycles@25%) | Terminal Adapter: | No | |
| | (11) | SOCI: | No | |
| | | Ventilation: | Central | |
| STD. DIMENSIONS | | Filter: | 2 Filters | |
| Length (mm ± 2): | 306 | Lateral Plug: | No | |
| Width (mm ± 2): | 192 | PLUGS | | |
| Height (mm ± 2): | 192 | Type: 1 x Vent S | ealed | BLACK |
| Total Weight (kg ± 5% | 6): 19.50 | HANDLES | | |
| | | Type: None | | |
| | | OTHERS | | |
| | | Degassing Tube: | No | |
| All figures show nominal va and applicable European R | alues. Tolerances are according to EN50342 Regulations. | | | |