


CUSTOMER DATASHEET


Printed: 17/02/2022


Product Management
Transportation Europe

Central Article Code: D31074C38-A Created: 10/05/2018

Local Code: EB954 Modified: 31/07/2020







Final Outlook D3138-A Approval date 01/07/2018

PERFORMANCES			
Voltage (V):	12 V		
C20 (Ah):	95.0	20 h	
Cranking (A):	760	EN	
Charge:	WET		
Technology:	Vented/F	Vented/Flooded	
Grid:	Ca/Ca		
Vibration:	V1 (30Hz	V1 (30Hz+/-2Hz/3g/2h)	
Endurance:	E1 (180 d	E1 (180 cycles@25%)	
STD. DIMENSIONS			

Type:	D31	BLACK
Hold Down:	Korean B1	
H.D. Adapter:	No	

CONTAINER

Type: Flat/Press integrated BLACK
Polarity: ETN 0
Terminals: EN taper post
Terminal Adapter: No
SOCI: No

Ventilation: Central
Filter: 1 Filter at Right
Lateral Plug: No

 Length (mm \pm 2):
 306

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 20.60

PLUGS

Type: 1 x VCL Vent BLACK

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

C.O from D31074C04-A(Grey lid to Black)