


CUSTOMER DATASHEET


Printed: 30/09/2021


Product Management
Transportation Europe

Central Article Code: D06105G09-A Created: 30/03/2017

Local Code: ED2103 Modified: 05/09/2018







Final Outlook D0609-A Approval date 15/06/2013

	7			N A	A	N		_	c
	RF	u	ĸ	IVI	А	N	u	⊏;	č

Voltage (V): 12 V

C20 (Ah): 210.0 20 h Cranking (A): 1050 EN

Charge: CHARGED

Technology: GEL Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 200 cycles@100%

CONTAINER

Type: D06 BLACK Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 518

 Width (mm \pm 2):
 274

 Height (mm \pm 2):
 240

 Total Weight (kg \pm 5%):
 63.50

PLUGS

Type: 6 x M18 Valve GREY MEDIUM

HANDLES

Type: 2 x Rope (Rigid holder) BLACK

OTHERS

Degassing Tube: No

Ge

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

D06103G09-A with GC pos & tank formation