


# **CUSTOMER DATASHEET**


Printed: 18/02/2022


Product Management
Transportation Europe

Central Article Code: LB3066C39-B Created: 05/06/2013

Local Code: EL652 Modified: 31/07/2020







Final Outlook LB339-B Approval date 15/09/2012

PERFORMANC	E٤
------------	----

Voltage (V): 12 V

C20 (Ah): 65.0 20 h Cranking (A): 650 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: EN-EFB Requirement

## CONTAINER

Type: LB3 BLACK

Hold Down: B13 H.D. Adapter: No

#### COVER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Central

Filter: 1 Filter at Right

Lateral Plug: No

### **STD. DIMENSIONS**

 Length (mm  $\pm$  2):
 278

 Width (mm  $\pm$  2):
 175

 Height (mm  $\pm$  2):
 175

 Total Weight (kg  $\pm$  5%):
 16.20

#### **PLUGS**

Type: 1 x Vent Sealed PSL-OE ha BLACK

### **HANDLES**

Type: 2 x PSL OE Integrated BLACK

### **OTHERS**

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.