


Central Article Code: LB4073C06-B

Created: 05/06/2013

Local Code: EL752

Modified: 31/07/2020



Final Outlook	LB406-B
Approval date	15/09/2012

PERFORMANCES

Voltage (V):	12 V	
C20 (Ah):	75.0	20 h
Cranking (A):	730	EN
Charge:	WET	
Technology:	Vented/Flooded	
Grid:	Ca/Ca	
Vibration:	Manufactured Specific	
Endurance:	EN-EFB Requirement	

STD. DIMENSIONS

Length (mm ± 2):	315
Width (mm ± 2):	175
Height (mm ± 2):	175
Total Weight (kg ± 5%):	18.60

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	LB4	BLACK
Hold Down:	B13	
H.D. Adapter:	No	

COVER

Type:	Double with Integrat	BLACK
Polarity:	ETN 0	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Central	
Filter:	1 Filter at Right	
Lateral Plug:	No	

PLUGS

Type:	1 x Vent Sealed PSL-OE ha	BLACK
-------	---------------------------	-------

HANDLES

Type:	2 x PSL OE Integrated	BLACK
-------	-----------------------	-------

OTHERS

Degassing Tube:	No
-----------------	----