


CUSTOMER DATASHEET


Printed: 15/09/2021


Product Management
Transportation Europe

Central Article Code: D05090A22-A Created: 08/06/2010

Local Code: EP1500 Modified: 23/07/2018







Final Outlook D0522-A Approval date 15/06/2010

PERFORMANCES				
Voltage (V):	12 V			
C20 (Ah):	180.0	20 h		
Cranking (A):	900	EN		
Charge:	CHARGED	CHARGED		
Technology:	AGM	AGM		
Grid:	Ca/Ca	Ca/Ca		
Vibration:	V1 (30Hz+	V1 (30Hz+/-2Hz/3g/2h)		
Endurance:	300 cycles	300 cycles@75%		

COVER				
H.D. Adapter:	No			
Hold Down:	B0			

CONTAINER

BLACK

D05

Type: Double without Hand BLUE LIGHT Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 1 Filter
Lateral Plug: No

Type:

STD.	DIMENSIONS

 Length (mm \pm 2):
 513

 Width (mm \pm 2):
 223

 Height (mm \pm 2):
 223

 Total Weight (kg \pm 5%):
 50.00

	PLU	JGS

Type: 1 x Valve+Cover BLUE LIGHT

HANDLES

Type: 2 x Rope (Rigid holder) BLACK

OTHERS

Degassing Tube: No

DNV-GL type approved 2015

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in

writing by EXIDE Technologies.