


TECHNICAL DATASHEET


05/11/2013 Printed:

Product Management Transportation Europe


Central Article Code: G34075M01-A

06/09/2005 ETN Code or Other: Modified: 6/26/2013





Created:



Final Outlook G3401-A Approval date 01/11/2010

PERFORMANCES					
Voltage (V):	12 V				
C20 (Ah):	50.0	20 h			
Rc (min):	0				
Cranking (A):	750	EN			
Vibration:	V3+ (35Hz/6g/60h)				
Endurance:	500 cycl	es@75%			
Charge:	CHARG	ED			
Technology:	Orbital				
Grid:	Pb-Sn				

Type:	G34	BLACK
Hold Down:	B7	
H.D. Adapter:	No	

CONTAINER

COVER

Maxxima/Orbital Type: **BLUE LIGHT**

Polarity: ETN 1

Terminals: SAE M 3/8"- 5/16" taper&stud

Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters Lateral Plug: No

WEIGHT AND STD. DIMENSIONS

Lead Weight (kg): 13.60 Battery Weight (kg): 18.64 Volume acid (I): 0.00 Length (mm): 260 Width (mm): 173 Height (mm): 206

Type:	6 x Valve+Cover	BLACK

HANDLES BLACK Type: 2 x Integrated

OTHERS

PI UGS

Degassing Tube: No

3/8-5/16 nuts in plastic bag

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.