




TECHNICAL DATASHEET

Printed: 28/10/2014
Product Management
Transportation Europe

Central Article Code: G34080M02-A Created: 06/09/2005 ETN Code or Other: Modified: 04/03/2014







Final Outlook G3402-A Approval date 01/10/2005

	PERFORMANC	ES	
Voltage (V):	12 V		
C20 (Ah):	50.0	20 h	
Rc (min):	0		
Cranking (A):	800	EN	
Vibration:	V3+ (35Hz/6g/60h)		
Endurance:	E3 (144 cycles@50%)		
Charge:	CHARGE	D	
Technology:	Orbital		
Grid:	Pb-Sn		
WEIGHT AND STD. DIMENSIONS			

Type:	G34	BLACK
Hold Down:	B7	
H.D. Adapter:	No	

CONTAINER

COVER

- уре:	Maxxima/Orbital BLACK

Polarity: ETN 9

Terminals: SAE S 3/8" side Terminal

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters
Lateral Plug: No

 Battery Weight (kg \pm 5%):
 17.9

 Volume acid (l \pm 5%):
 .0

 Length (mm \pm 2):
 260

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 206

Туре:	6 x Valve+Cover	BLACK

HANDLES				
Type:	2 x Integrated	BLACK		
OTHERS				
Degassing Tube:	No			

PLUGS

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.