



PROMOTIVE BLACK

Key benefits

- Ideal for vehicles with lower energy requirements
- Standard OE technology and low water consumption enables entry level to reduce TCO
- Meets EN requirements (EN 2) standard and vibration resistance (V1)



For more information visit www.varta-automotive.com




ORDER INFORMATION

| | |
|--------------------------|-------------------|
| European Type No. (ETN): | 690 033 120 |
| Article Number: | 690 033 120 A74 2 |
| Barcode: | 0 |
| Packaging Unit: | 1 |
| Quantity per Pallet: | 21 |

TECHNICAL INFORMATION

| | | | |
|-----------------------------------|------|---------------------|--------|
| Voltage [V]: | 12 | Base Hold-down: | B03 |
| Battery Capacity [Ah]: | 190 | Layout: | 4 |
| Cold Cranking Amps (CCA), EN [A]: | 1200 | Terminal Types: | 1 |
| Length [mm]: | 513 | Case Size: | B |
| Width [mm]: | 223 | Weight filled (kg): | 44,990 |
| Height [mm]: | 223 | | |

DRAWINGS



| Criteria | Promotive EFB | Promotive Silver | Promotive Blue | Promotive Black |
|--|---|--|--|----------------------|
| No. of Battery Types | 2 | 3 | 5 | 36 |
| Primary Function | Engine start and high energy demand, including Hoteling | Engine Start and Enhanced Power Supply | Engine Start and Enhanced Power Supply | Engine Start |
| Reduction potential in Total Cost of Ownership (TCO) | Best | Best | Better | Good |
| Technology | Enhanced Flooded | Conventional Flooded | Conventional Flooded | Conventional Flooded |
| Grid Alloy | Calcium/Calcium | Calcium/Calcium | Calcium/Calcium | Calcium/Calcium |
| Vibration Resistance | EN V4 Standard | EN V3 Standard | EN V2 Standard | EN V1 Standard |
| Quality Level | Original Equipment | Original Equipment | Original Equipment | Original Equipment |
| Water Consumption | Extremely Low | Extremely Low | Very Low | Very Low |