V1. 04/18



... connecting to the aftermarket

CTSMT004.2

Mitsubishi Steering Wheel Control Interface





Vehicle Application

Mitsubishi Colt (Z30) 2009 - 2012

For Non Amplified Vehicles

Key Features

Retains Steering Wheel Controls (if equipped)
Allows Access to Trip Computer Settings





The information provided in this document is subject to change without notice due to manufacturer changes and/or improvements to the product/s.

ABOUT THIS PRODUCT

CTSMT004.2

Analogue Steering Wheel Control Interface for select non-amplified Mitsubishi vehicles with Mitsubishi Electric original stereo

WIRING COLOUR CODES

Purple	Right Rear Speaker +
Purple/Black	Right Rear Speaker -
Green	Left Rear Speaker +
Green/Black	Left Rear Speaker -
Grey	Right Front Speaker +
Grey/Black	Right Front Speaker -
White/Black	Left Front Speaker - Left Front Speaker -

Yellow Red Black Permanent 12V Ignition 12V Connect to Ground

NB: Flying Black Ground wire must be connected to a suitable ground source in the vehicle

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.**

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.



FITTING GUIDE

1. Remove and disconnect the original head unit.

2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.



www.connects2.com

FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

STEERING WHEEL CONTROL FUNCTIONALITY

Original Button	Function
+ Icon	Volume +
- Icon	Volume -
Up Arrow	Track +
Down Arrow	Track -
MODE	Source

Trip Computer Settings

- 1. Press 'MODE' once for source.
- 2. Press 'MODE' for 2 seconds to cycle through trip computer settings.
- 3. Press and hold 'MODE' to reset on any trip computer settings screen.