

...connecting to the aftermarket

CTSDC001.2

Dacia Steering Wheel Control Interface









Vehicle Application

Dacia Duster (SD/SR) 2010 - 2012 Dacia Sandero 2010 - 2012

Key Features

- Retains Steering Wheel Controls (if equipped)
 - Retains OEM Phone Buttons (if equipped)





ABOUT THIS PRODUCT

CTSDC001.2

Analogue steering wheel control interface for select Dacia vehicles.

WIRING COLOUR CODES

Yellow **Purple** Right Rear Speaker + Purple/Black Right Rear Speaker -Black Green Left Rear Speaker + Red Green/Black Left Rear Speaker -Grey Right Front Speaker + Grey/Black Right Front Speaker -White Left Front Speaker + White/Black Left Front Speaker -

PRIOR TO INSTALLATION

NB: Interface Dipswitch can be set to change SWC functionality. See Page 4 for details.

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. Connects2 can not be held responsible for the installation of this product.

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at support.connects2.com and provide as much information as possible.

FOLLOW US ON SOCIAL MEDIA for all the latest updates



/CONNECTS2
Watch us on YouTube



Like us on facebook



CONNECTS2LTD Follow us on instagram







Permanent 12V

Ground

Ianition 12V

FITTING GUIDE

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.





FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the corresponding male vehicle connectors from the vehicle.

Test head unit for correct operation.

STEERING WHEEL CONTROL FUNCTIONALITY

NB: Steering wheel control functions can be adjusted through changing the position of Dipswitch 1 inside the interface box. Open the plastic casing and set the Dipswitch according to your preferences prior to installation. See below for information:

Type A Set Dip. 1 to 'OFF'



- A. SourceB. Source
- **C**. Vol +
- **D.** Pick Up/Hang Up
- E. Vol -
- **F.** FM/Band
- **G.** Track + / Track -
- C + E. Mute

Type B Set Dip. 1 to 'ON'



- 1. Source
- **2.** Pick Up/Hang Up
 - 3. Vol+
- **4.** FM/Band
- **5.** Vol -
- 6. Track + / Track -
- **3 + 5.** Mute