

...connecting to the aftermarket

# **CTSRN005.2**

# Renault & Nissan Steering Wheel Control Interface









## **Vehicle Application**

Renault Clio (III, R) 2005 - 2009
Renault Megane (II) 2005 - 2008
Renault Scenic (JM/JZ) 2005 - 2009
Renault Laguna (II, III, G) 2005 - 2009
Renault Modus 2004 - 2012
Renault Twingo (II) 2007 - 2009
Renault Trafic (II) 2006 - 2010
Renault Kangoo (II, W) 2008>
Renault Master (III) 2010>
Nissan Primastar (X83) 2008 - 2010

## **Key Features**

Retains Steering Wheel Controls





#### **ABOUT THIS PRODUCT**

#### CTSRN005.2

CAN-Bus Steering Wheel Control Interface for Renault and Nissan vehicles with OEM dashboard display, VDO Update List original stereo and 8 Way ISO connector

Yellow

Black

Red

#### WIRING COLOUR CODES

**Purple** Right Rear Speaker + Purple/Black Right Rear Speaker -Green Left Rear Speaker + Green/Black Left Rear Speaker -Grev Right Front Speaker + Grey/Black Right Front Speaker -White Left Front Speaker + White/Black Left Front Speaker -

Permanent 12V Ground Ignition 12V

#### PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.** 

#### TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.

# FOLLOW US ON SOCIAL MEDIA for all the latest updates



/CONNECTS2
Watch us on YouTube



/CONNECTS2
Like us on facebook



CONNECTS2LTD
Follow us on instagram







#### **FITTING GUIDE**

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.





#### FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

## STEERING WHEEL CONTROL FUNCTIONALITY

