




Central Article Code: L06093A05-D

Local Code: EK1060

Created: 31/01/2022

Modified: 21/09/2022



Final Outlook	L0605-D
Approval date	01/12/2017

PERFORMANCES

Voltage (V):	12 V	
C20 (Ah):	106.0	20 h
Cranking (A):	950	EN
Charge:	CHARGED	
Technology:	AGM	
Grid:	Ca/Ca	
Vibration:	Manufactured Specific	
Endurance:	E4 EN50342-6	

STD. DIMENSIONS

Length (mm ± 2):	392
Width (mm ± 2):	175
Height (mm ± 2):	190
Total Weight (kg ± 5%):	29.00

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	L06	BLACK
Hold Down:	B13	
H.D. Adapter:	No	

COVER

Type:	Double with Integrat	BLACK
Polarity:	ETN 0	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Central	
Filter:	2 Filters	
Lateral Plug:	Standard shape	Left side BLACK

PLUGS

Type:	1 x Vent Sealed (Valve)	BLACK
-------	-------------------------	-------

HANDLES

Type:	2 x Integrated	BLACK
-------	----------------	-------

OTHERS

Degassing Tube:	No
-----------------	----