


## **CUSTOMER DATASHEET**


Printed: 25/11/2022


Product Management
Transportation Europe

Central Article Code: L04084A14-D Created: 31/01/2022

Local Code: EK820 Modified: 21/09/2022







Final Outlook L0414-D Approval date 15/10/2013

| P | F | R | F | O | R | M   | Δ | N | C | F | S |
|---|---|---|---|---|---|-----|---|---|---|---|---|
|   | _ |   |   | u | • | IVI | _ |   | v | _ | • |

Voltage (V): 12 V

C20 (Ah): 82.0 20 h Cranking (A): 800 EN

Charge: CHARGED

Technology: AGM Grid: Ca/Ca

Vibration: Manufactured Specific

Endurance: E4 EN50342-6

## COVER

L04

B13

No

Type: Double with Integrat BLACK

**CONTAINER** 

Polarity: ETN 0

Type:

Hold Down:

H.D. Adapter:

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters

Lateral Plug: Standard Right side BLACK

shape

## **STD. DIMENSIONS**

Length (mm ± 2): 315

Width (mm  $\pm$  2): 175 Height (mm  $\pm$  2): 190 Total Weight (kg  $\pm$  5%): 23.30

| | |

Type: 1 x Vent Sealed (Valve)

BLACK

**BLACK** 

## **HANDLES**

**PLUGS** 

Type: 2 x Integrated BLACK

**OTHERS** 

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.