







SPRAYFIxx-solvent-1 I

Adjusting nozzle

 Item number:
 06 911 001

 EAN:
 4103810069116

Discount group: A

Technical data

Container volume max. (ml): 1000 Filling volume max (ml): 800

Colour of container: white, transparent

Temperature range (°C): +5 / +30
Operating pressure max. (bar): 2,5
Height (mm): 290
Base LxB (mm): 230 x 110
Weight (kg): 0,42

Nozzle: regulating nozzle with plastic adjustment nut

PA (80 685)

Spray pattern: punctual jet = full jet + cone jet = spray jet

Spraying quantity with full jet (ml/min): 480
Spraying quantity with spray jet (ml/min): 192
Spraying distance with full jet (m): 4,6
Spraying distance with spray jet (m): 0,8
Colour code: black

Materials

Container: HDPE (high density polyethylene)

Seals: Viton® (FKM)

Pump head: PA

Valve rod + springs: brass / stainless steel

Nozzle: PA

Specification

- HDPE container with scale in ml
- According to application, spray pattern and slewability, the following nozzles are available: adjusting and swivelling nozzle, brass (80 680) + flat spray nozzle 110° PA (80 682), refer to SPRAYFIxx Solvent (80 687) nozzle kit
- Seals Viton® FKM
- Manual pressure build-up with combined overpressure and venting valve
- With EAN bar code

Special notes

- Suitable for solvents, except acetone, as long as the material of the sprayer is resistant to these media
- Different nozzles allow for application-specific use
- Colour coding at container and pump head, black
- UV-resistant

Packaging

Packing unit: 1.0